

Note:

All steel parts such as small fittings to be galvanized by hot process.
Quantity shown in one boat.

	Y.Kado	NO.	-	.	4 4				00 60	ľ	Ш	12				17		20		3 23	Ш		27		29		32	_	\perp	Ш	37		Ш	41				46				51 02	1			\perp		50 00
	Y.Kimura M.Takamura NTS	TICULARS	Engine	Screw Shaft	Screw Droneller	Fuel Oil Tank	Exhaust Pipe	Steering Wheel	Rudder Stock	Shoe Piece	Emergency Tiller	Controller	Breather Valve	Keel Bracket	Releasing Handle	Releasing Cable	Locker	Embarkation Hatch	Access Hatch	Fender Boot Skoto	Window	Hand Rail	Life Line	Hydraulic System	Clip	Wire Stopper	Through Plug	Painter Release Device	Fresh Water Locker	Bottom Plug	Crutch Stand	Engine Casing	Center Seat	Console Box	Battery	Ceiling Light	Canopy Light	Stern Tube	Air Reservoir	Alr Regulator	Difference Meter	Spray Pump	Water main	Water main	Water main	Head Support	Center Seat B ^{HD}	Flushing With Can
	NO.	SIZE	18.4kW	φ35	430 × 300	67	32A	φ 365	φ39	12t	φ 25	*	φ50	19t	20A	JC.	£ 5t	6t	65	D-40	6t	φ 25	φ4 60		φ17.5	12t	φ6	16t	¥ 5	φ32	20A	£ 5£	5t	5t	DC12V	8~10W	8~10W	ф 70	501 it	φ6	4	96	φ60	φ60	φ 60			
		MATL		SUS304	AC/A-F	SS400	ADS		SHS304	SS400		C	BC	SS400	SGP	303304	FRP	FRP	FRP	Rubber	A6063S	SUS304	SUS304		BC BC	SS400	BC	BC 7	쁑	ВС	SGP	FRP	FRP	FRP				SS400	Low Ally St.	Bs BM	Ş.	B	A6063	A6063	A6063	:	AL & P W	
co	GENERAL	QUNT'Y	-		1 set	2	1	1	-	-	1	1set	1 2	2	1	2 Iset	3	2	2	1set	4	1set	2sets	1	12	۵	_	- -	- -	_		-	-	_ -	2	2	1	_ -		_	_ -	- -		1set	1set	1set		
8. 0M TYPE	AL ARRANGEMENT - 殼配置図	REMARKS	Yanmar 3JH30A		With Greased Packing	Both side	with Anti-Swamp Valve		with Emergency Tiller	-		Type: AS20H		with Pin and Set Bolt			with Proper Openings	with Hinge	with Hinge		Toughenend glass					for Lashing Wire Rope	for Davit Control Wire	for Painter	3 liters per Derson	Automatic											of parolicae	for Barometer			Inree(3) Point Type			